



COPERNICUS II GPS RECEIVER

KEY FEATURES

- 2.54 mm T x 19 mm W x 19 mm L
- -160 dBm tracking sensitivity
- 120 mW typical continuous tracking
- Supports SBAS (WAAS, EGNOS)
- Active or passive antennas
- NMEA, TSIP, TAIP protocols
- RoHS-Compliant (Pb-free)
- 2G dynamics

ULTRA-THIN, LOW POWER, SURFACE MOUNT GPS MODULE

Drop-in Performance

The Trimble® Copernicus® II GPS receiver delivers proven performance and Trimble quality for a new generation of position-enabled products. It features the TrimCore™ navigation software for extremely fast startup times and high performance in foliage canopy and urban canyon environments.

The Copernicus II is fully compatible with all applications using previous generation of Copernicus module. The Copernicus II module is a complete 12-channel GPS receiver in a 19 mm x 19 mm x 2.54 mm thumbnail-sized module. The module is packaged in tape and reel for high speed pick-and-place manufacturing processes; 28 edge castellations provide RF and I/O interface without the need for connectors. Each module is manufactured and tested to Trimble's highest quality standards.

The sensitive Copernicus II GPS receiver can autonomously acquire GPS satellite signals and quickly generate reliable position fixes in extremely challenging environments and under poor signal conditions. The unit also accepts aided GPS (A-GPS) data for faster startups in very weak conditions.

The Copernicus II GPS module is a complete drop-in, ready-to-go receiver that provides position, velocity, and time data in a user's choice of three protocols. Trimble's powerful TSIP protocol offers complete control over receiver operation and provides detailed satellite information. The TAIP protocol is an easy-to-use ASCII protocol designed specifically for track and trace applications. The bi-directional NMEA 0183 v3.0 protocol offers industry-standard data messages and a command set for easy interface to mapping software.

Applications

Compatible with active or passive antennas, the Copernicus II GPS receiver is perfect for portable hand-held, battery-powered applications. The receiver's small size and low power requirement make it ideal for use in portable appliances, sport accessories, personal navigators, cameras, computer, and communication peripherals, as well as vehicle tracking, navigation, and security applications.



COPERNICUS II GPS RECEIVER

PERFORMANCE SPECIFICATIONS

Accuracy (24 hr static)

Horizontal	<2.5 m 50%, <5 m 90%
SBAS	<2.0 m 50%, <4 m 90%
Altitude	<5 m 50%, <8 m 90%
SBAS	<3 m 50%, <5 m 90%
Velocity	0.06 m/sec
Static PPs	+/- 60ns RMS
PPS (Stationary Mode "indoor" @ -145dBm)	+/-350ns

Acquisition (Autonomous, -130dBm, 50%)

Reacquisition	2 s
Hot Start	3 s
Hot Start without battery backup	8 s*
Warm Start	35 s
Cold Start	38 s

Sensitivity (unaided)

Tracking	-160 dBm
Acquisition	-146 dBm

Receiver Dynamics 2G

* Ephemeris not older than 4 hours.

INTERFACE CHARACTERISTICS

Connections	28 surface-mount edge castellations
Serial Port	2 serial ports
PPS	3.0 V CMOS-compatible, TTL-level pulse, once per second
Protocols	TSIP, TAIP, NMEA 0183 v3.0 Bi-directional NMEA messages Messages selectable by NMEA commands Selection stored in flash memory

ELECTRICAL CHARACTERISTICS

Prime Power	+2.7 V DC to 3.3 V DC
Power Consumption	(typ.) 40 mA (120 mW) @ 3.0 V
Backup Power	+2.7 V DC to +3.3 V DC
Ripple Noise	Max 50 mV, peak-to-peak from 1 Hz to 1 MHz

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40 °C to +85 °C
Storage Temperature	-55 °C to +105 °C
Vibration	0.008 g/Hz 5 Hz to 20 Hz 0.05 g/Hz 20 Hz to 100 Hz -3 dB/octave . . . 100 Hz to 900 Hz
Operating Humidity	5% to 95% R.H. non-condensing, at +60 °C

PHYSICAL CHARACTERISTICS

Enclosure	Metal shield
Dimensions	19 mm W x 19 mm L x 2.54 mm H (0.75" W x 0.75" L x 0.1" H)
Weight	<2 grams (0.07 ounce) including shield

PINOUT ASSIGNMENTS

GND	1	28	GND
GND	2	27	GND
RF-IN	3	26	Reserved
GND	4	25	Reserved
LNA	5	24	TXD-B
VBAT	6	23	TXD-A
Open	7	22	Reserved
Short	8	21	RXD-A
Reserved	9	20	RXD-B
Reserved	10	19	PPS
Xreset	11	18	Reserved
Vcc	12	17	Reserved
GND	13	16	Xstandby
GND	14	15	GND

ORDERING INFORMATION & ACCESSORIES

- Module Copernicus GPS Receiver Module, available as Single modules
Tape on reel (100 pieces)
Tape on reel (500 pieces)
- Reference Board Copernicus GPS module mounted on a carrier board with I/O and RF connectors, including the RF circuitry with the antenna open detection, as well as antenna short detection and protection.
- Starter Kit Includes Copernicus Reference Board mounted on interface motherboard in a durable metal enclosure, AC/DC power converter, compact magnetic-mount GPS antenna, ultra-compact embedded antenna, USB interface cable, cigarette lighter adapter, TSIP, NMEA, and TAIP protocols, software toolkit and manual on CD-ROM

Ultra-Compact Embedded Antenna
3.3 V active miniature unpackaged antenna
Cable length: 8 cm
Dim: 22 mm W x 21 mm L x 7.5 mm H
(0.866" x 0.827" x 0.295")
Connector: HFL



Compact Magnetic-Mount Antenna, MCX or SMA
3V active micropatch antenna with magnetic mount
Cable length: 5 m
Dim: 34 mm W x 37.4 mm L x 12.95 mm H
(1.34" x 1.47" x 0.51")
Connectors: MCX or SMA



Parts of this product are patent protected.

Trimble has relied on representations made by its suppliers in certifying this product as RoHS compliant.

Specifications subject to change without notice.

Trimble Navigation Limited is not responsible for the operation or failure of operation of GPS satellites or the availability of GPS satellite signals.

NORTH AMERICA
Trimble Navigation Limited
Corporate Headquarters
935 Stewart Drive
Sunnyvale, CA 94085
Phone: +1-800-787-4225
Phone: +1-408-481-7741
Email: AD_Sales@trimble.com

EUROPE
Trimble Navigation Europe
Phone: +49-6142-2100-161

KOREA
Trimble Export Ltd, Korea
Phone: +82-2-555-5361

CHINA
Trimble Navigation Ltd, China
Phone: +86-21-6391-7814

TAIWAN
Trimble Export Limited, Taiwan
Phone: +886-02-85096574

